


ASTRA RAILINNG FENCE





STVS MODULAR

- o Free maintenance. Low cost using
- o STVS Modular professional coating know-how give 5 and 10 years corrosion warranty that minimize the cost of the fence.
- o Impossible to remove the panel once installed.
- o Painted inside horizontal bar enhance corrosion prootection.

BEAUTIFUL

- Elegant looks that enhance the beauty of the site.
- Stainless steel connector give strong and smooth appearance.
- High-end architecture powder coating finish.
- UV resistant reduce fading color.

EASY TO INSTALL

- Modular design that allow easy & quick installation
- o Applicable for all types of configurations: Curves, Corners, Slopes, walls... with the same standard products.



14


*** DESIGN OPTIONS:**







2 HORIZONTAL BARS

3 HORIZONTAL BARS








INFILL


HORIZONTAL BAR


POST SECTION














NON **OVERSTANDING**


OVERSTANDING

OVERSTANDING WITH PRESS SPEAR



15





BURRIED INTO GROUND

Max height: 2.5m Recommend increase post section 75x75mm if 2.5mH = < H < = 3m


ON THE FLANGE

Max Height: 2.0m Recommend burried post if H>2mH









INSTALLATION PRINCIPAL

G1 :	STVS standard polyester powder coating.
G1 Plus:	Primer paint + STVS standard polyester powder coating.
G2:	Hot dip galvanized.

ANGLE MANAGEMENT

Standard Color: (Other color available upon the request)



FINISHING

DESIGN NOTED:

- Standard post distant for **ASTRA** railing fence: **2500mm** and heigh <2100mm
- Standard post distant for **ASTRA** railing fence: **2000mm** and heigh >2100mm
- Only paint finishing for OVERSTANDING WITH PRESS SPEAR design



*** WARRANTY:**

STVS MODULAR WARRANTY MATRIX - <u>ASTRA</u> RAILING								
PAINTING SPECIFICATION		C2	C3	C4	C5	C5M		
		Temperate low pollution Countryside. >20Km from sea side	Urban and industrial atmospheres, moderate pollution or low salinity. > 20Km from sea side	Industrial areas or coastal areas with moderate salinity. From 3 to 20 Km from seaside	Industrial, high humidity, aggressive atmosphere. From 0.5 to 3 Km from seaside	Coastal and offshore areas with high salinity. Less than 0.5 Km from seaside		
ASTRA FENCE Tolerances for the anticorrosion guarantee are defined based on ISO 4628-3 for the degree of rusting grade and ISO 4628-2 for the degree of blistering.	G1	5	5	3	N/A	N/A		
	G1 Plus	10	10	10	5	2		
	G2	10	10	10	10	5		

Noted:

^{*} Corrosion warranty are not applied for accessories parts

^{*}The anti-corrosion guarantee only covers rust-related faults. It is based on the European standard ISO 12944, which defines precise corrosivity categories.